

BEST AVAILABLE COPY

[c3]

3. (Currently Amended) The ~~connector~~ apparatus of claim 1 wherein said insulating spacer insert is comprised of a "U" shaped channel having with longitudinal side flanges for maintaining the first and second base ~~units~~ bases in line with respect to each other; and
~~said channel further being with a central fin narrower than said channel and centrally and vertically positioned in said channel to maintain said first stud portions portion a fixed distance from apart and in a fixed position relative to said second stud portion.~~
~~each other and to first and second base units.~~

[c4]

4. (Currently amended) The apparatus of claim 1 wherein:

said first conductive base has a selected length having first and second ends, a selected width and a selected thickness less than said selected width;

said second conductive base has a selected length having first and second ends, a selected width and a selected thickness less than said selected width;

~~a first portion of a~~ said first conductive stud portion secured to said first base at its second end;

~~a second portion of a~~ said second conductive stud portion secured to said second base at its second end;

said first and second conductive stud portions carrying mating thread patterns thereon;

said first side of said first base being electrically connected to said first terminal; and

said first side of said second base being electrically connected to said second terminal.

[c5]

5. (Cancelled) The apparatus of claim 4 wherein:

said first and second portions of said conductive stud are identical and carry mating thread patterns thereon.

BUR920030157US1 -3-

S.N. 10/707,169

Rule 1.21